Art. no.: 1220051



OX-ON Harness V5 Endeavour Supreme



Features:

- Extremely comfortable
- · Click-lock buckles
- · Surface treated against dirt
- Ergonomic back-support belt
- Padded at the back, shoulders and thighs.

Colours:

black, orange

Product Description:

OX-ON V5 Endeavour Harness Supreme L/XL is a top-class 2-point body harness for those who need an extremely comfortable harness with a handsome design, back-support belt for positioning and completely unique freedom of movement. You can use the OX-ON V5 Endeavour Harness Supreme harness for the vast majority of tasks and applications. Especially for, for example, scaffolding, roofing and mast work. The back support belt combined with a support line allows you to work using both hands. The harness's click-lock buckles make it incredibly easy for you to put on and off, and with six user-friendly adjustment points, you get a harness that is extremely easy to adjust so that it fits you perfectly. It gives you great flexibility when wearing the harness. At the same time, padding around the shoulders and at the back and thighs ensures that you have excellent working comfort when you wear the harness for a longer period of time. The body harness is equipped with a strong D-ring with a fall indicator on the back, and on the chest there are two more loops for anchoring. The belt is equipped with 2 straps and 2 rings, in which you can fasten tools etc. In addition, the ergonomic support belt is fitted with a D-ring on each side, where you can fasten a support line. The harness is made of strong, thoroughly tested and reflective 2-color webbing straps, which are surface-treated against oil and dirt, which makes the harness extremely dirt-repellent and easy to clean and maintain. The body harness is tested for 150 kg.

Sizes:

STR.	ART. NO.	EAN
2XL/3XL	1220052	6425670000756
L/XL	1220051	6425670000749
S/M	1220050	6425670000732

Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 stk	N/A	6 stk

EN standards	EN 358 EN 361 EN 361 Shape Sha
Certificates	C € CAT. III
Features	WEIGHT LOAD UP TO 150 KG