

Art. no.: 313.10

OX-ON Mask FFP1 NR D Basic



Features:

- Suitable for work in dusty environments
- Extremely low breathing resistance
- Affordable
- Aluminium nose bridge
- Latex-free elastic band
- 20 pcs. masks per box.

Colours:

white

Total CO2 emission:

0.067 Kg CO2 eq.

Materials:

Total water consumption:
0.009 m3 world eq.

Product Description:

OX-ON Mask FFP1NR D Basic is the safety approved filtrating single-use mask, which you can use when working with less hazardous dry particles and liquid aerosols with a Workplace Exposure Limit (WEL) <5 mg/m³ (max. concentration 4 x WEL).

You can for example use the affordable disposable mask when working with cardboard, textiles, feathers, graphite, clay, pollen, grinding of aluminium, plaster and quartz-free stone.

The mask is dolomite tested, which means that you get a filter with a particularly large dust capacity with slowly increasing resistance.

The sealing soft foam rubber at the nose as well as the mouldable aluminium nose bridge ensure you a perfect and comfortable adaptation to your face. The elastic band of the mask is latex-free.

You get 20 pcs. masks per box.

Sizes:

STR.	ART. NO.	EAN
One size	313.10	5701952313105

Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 æske	N/A	12 æske

EN standards	EN 149+A1
Certificates	CAT. III
Features	 ADJUSTABLE NOSE-CLIP