

Art. no.: 313.15

OX-ON Mask FFP2 NR D Basic



Features:

- Suitable for work in dusty environments
- Extremely low breathing resistance
- Affordable
- Aluminium nose bridge
- Latex-free elastic band
- 20 pcs. masks per box.

Colours:

white

Total CO2 emission:

0.07 Kg CO2 eq.

Materials:

Total water consumption:

0.01 m3 world eq.

Product Description:

OX-ON Mask FFP2NR D Basic is the safety approved filtrating single-use mask, which you can use when working with hazardous dry particles and liquid aerosols with a Workplace Exposure Limit (WEL) <5 mg/m³ (max. concentration 10 x WEL).

You can for example use the affordable disposable mask when you are grinding wood, metal, stone and plastic, and also when working with lead/copper-free paint as well as water-based colour spray paint.

The mask is dolomite tested, which means that you get a filter with a particularly large dust capacity with slowly increasing resistance.

The sealing soft foam rubber at the nose as well as the mouldable aluminium nose bridge ensure you a perfect and comfortable adaptation to your face. The elastic band of the mask is latex-free.

You get 20 pcs. masks per box.

Sizes:

STR.	ART. NO.	EAN
One size	313.15	5701952313150

Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 æske	N/A	12 æske

EN standards	
Certificates	
Features	