

Art. no.: 313.16

## OX-ON Mask FFP2 NR D Basic



### Features:

- Suitable for work in dusty environments
- Extremely low breathing resistance
- Affordable
- Aluminium nose bridge
- Latex-free elastic band
- 2 pcs. masks per box.

### Colours:

white

### Total CO2 emission:

0.07 Kg CO2 eq.

### Materials:

### Total water consumption:

0.01 m3 world eq.

### Product Description:

OX-ON Mask FFP2NR D Basic is the safety approved filtrating single-use mask, which you can use when working with hazardous dry particles and liquid aerosols with a Workplace Exposure Limit (WEL) <5 mg/m<sup>3</sup> (max. concentration 10 x WEL).

You can for example use the affordable disposable mask when you are grinding wood, metal, stone and plastic, and also when working with lead/copper-free paint as well as water-based colour spray paint.

The mask is dolomite tested, which means that you get a filter with a particularly large dust capacity with slowly increasing resistance.

The sealing soft foam rubber at the nose as well as the mouldable aluminium nose bridge ensure you a perfect and comfortable adaptation to your face. The elastic band of the mask is latex-free.



You get 2 pcs. masks per box.

### Sizes:

STR.	ART. NO.	EAN
One size	313.16	5701952313167

### Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 pk	N/A	72 pk

EN standards	
Certificates	
Features	