Art. no.: 355.70



OX-ON Fall Protection Kit Supreme V53 L/XL



Features:

- Complete set
- Exclusive harness with ergonomic back-support belt
- Edge-tested work line
- User-friendly click-lock buckles
- · Slide lock of stainless steel

Colours:

black, red

Product Description:

OX-ON Fall Protection Kit Supreme is a very user-friendly and exclusive fall protection kit that is suitable for those who have demanding work tasks involving, for example, scaffolding, roofing or working on masts, where you may be in a fixed working position for a long time. The bag contains OX-ON V53 Harness Supreme L/XL: A top-class 2-point body harness with click-lock buckles and a back-support belt. OX-ON Fall Arrester Supreme: An effective fall arrester with 10 meters of abrasion-resistant edge-tested work line and stainless steel slide lock. OX-ON Webbing Sling Comfort 1.2 m: An anchoring strap for the fall protection. The OX-ON V53 Body Harness adjusts quickly and perfectly to the body with a number of adjustment points, so you are guaranteed maximum comfort and freedom of movement in your work. The effective click-lock buckles make it easy for you to put the harness on and take it off, and a strong D-ring on the back and at the chest ensures you a good and solid anchoring - as well as an easy connection. The OX-ON V53 Body Harness is also equipped with an ergonomic back belt that gives you optimal support and comfort in connection with your work. On each side of the support belt there is a D-ring where you can fasten a support line, and at the same time the belt is designed so that you can fasten tools in the corresponding rings. The harness is made of a robust 2-color webbing strap, and it has been tested to 150 kg. With OX-ON Fall Arrester Supreme, you get an effective fall arrester package and a durable stainless steel rope slide lock

Sizes:

STR.	ART. NO.	EAN	
L/XL	355.70	6425670011356	

Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 stk	N/A	6 stk

EN standards	EN 353-2 EN 354 EN 358 EN 361 EN 362 EN 795 EN 566 EN 353-2 S 566 EN 353-2 EN 354 EN 361 EN 362 EN 795 EN 566 EN 795 EN 566
Certificates	C CAT. III REACH
Features	EDGE TESTED PY 0,5mm) EDGE TESTED



Product Description:

with auto-lock carabiner mounted on a 10 meter edge-tested kernmantle (12 mm) with great abrasion resistance, and with properties that make the rope unable to twist. The rope and slide lock give you freedom of movement and safety at the same time, as the rope slider brakes you instantly in the event of a fall. The rope is for vertical use, and the fall arrester package releases a maximum energy absorber of 1 meter. The lower part of the rope should be attached or equipped with a counterweight. OX-ON Webbing Sling Comfort 1.2 meters gives you a compact and fast solution when you need to anchor your fall protection. The polyester strap is 26 mm wide, it takes up minimal space and it is extremely easy to use. The webbing strap has a tensile strength of >30kN You get the whole set in the practical OX-ON Backpack size M. 25x42 cm. The anchorage point should, if possible, be above head height to reduce the ground clearance. Note that the ground clearance must be calculated at all times before starting work with fall protection. For further information on the required ground clearance, refer to the enclosed user manual or contact OX-ON.