

Art. no.: 355.90

OX-ON Fall Protection Kit Basic



Features:

- Complete set
- Lightweight body harness
- Kernmantle rope
- Cost-friendly
- Slide lock of galvanized steel

Colours:

black, green

Product Description:

OX-ON Fall Protection Kit Basic is an economically attractive standard fall protection set that is suitable for, for example, scaffolding, facade or roof work.

The bag contains OX-ON C3 Harness Basic L/XL: A lightweight body harness with classic buckles. The body harness is also tested for 150 kg. OX-ON Fall Arrester Basic 10 m: A fall arrester with a 10 m rope and a slide lock of galvanized steel. OX-ON Webbing Sling Comfort 1.2 m: An anchoring strap for the fall protection.

The body harness OX-ON C3 Harness Basic is easily adjusted to the body with classic buckles at the chest and thighs, so it sits comfortably on you and you have full freedom of movement in your work. The harness is equipped with a strong D-ring on the back and two loops on the chest, which ensures you a good and solid anchorage. With OX-ON Fall Arrester Basic you get a fall arrester package and a rope slide lock of galvanized steel with auto-lock carabiner mounted on 10 meter kernmantle rope (12 mm) with great abrasion resistance, and with properties so that the rope cannot twist. The rope and slide lock give you freedom of movement and safety at the same time, and brake you immediately in the event of a fall.

The rope is for vertical use, and the fall arrester package releases a maximum energy absorber of 1 meter. The lower part of the rope should be attached or equipped with a counterweight.

OX-ON Webbing Sling Comfort 1.2 meters gives you a compact and fast solution

Sizes:

STR.	ART. NO.	EAN
L/XL	355.90	6425670011363

Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 stk	N/A	8 stk

EN standards	<div>EN 353-2</div> <div>EN 354</div> <div>EN 361</div> <div>EN 566</div> <div>EN 795b</div>
Certificates	<div>CE</div> <div>CAT. III</div> <div>REACH</div>
Features	

Product Description:

when you need to anchor your fall protection. The polyester strap is 26 mm wide, it takes up very little space and it is extremely easy to use. The webbing strap has a tensile strength of >30kN

You get the whole set in the durable OX-ON Backpack size S. 36x28 cm

The anchorage point should, if possible, be above head height to reduce the ground clearance.

Note that the ground clearance must be calculated at all times before starting work with fall protection. For further information on the required ground clearance, refer to the enclosed user manual or contact OX-ON.