Art. no.: 91365



OX-ON Earmuffs BT1 Comfort



Features:

- Bluetooth
- Built-in microphone
- · Ventilated dual headband
- AUX input
- Moderate to high attenuation.

Colours:

black

Product Description:

OX-ON Earmuffs Bluetooth BT1 Comfort are robust, Bluetooth-enabled earmuffs for protection when working at moderate noise levels. The earmuffs are equipped with a practical built-in microphone, ensuring great audio quality for phone calls. AUX input allows you to connect devices such as an MP3 player. The integrated rechargeable battery and accessory USB cable make charging the earmuffs easy and hassle free. The dielectric plastic design provides high protection in an electrical environment. Thanks to the unique dual headband reducing pressure to the head, and a weight of just 353 grams, these earmuffs are incredibly light and comfortable to wear. OX-ON Earmuffs Bluetooth BT1 Comfort are also ideal to wear in hot weather when the ventilated inner headband provides increased breathability. You have the option of adjusting the headband to your own personal fit and positioning the snap-in ear pads as desired. The smart 'quick click' system ensures that your settings remain locked in place while you work. The cups are made of impact-resistant ABS material, which makes this hearing protection extra robust.

Inside is a special 2-layer foam that feels incredibly soft and provides a snug fit to your ears. OX-ON Earmuffs Bluetooth BT1 Comfort have an attenuation value (SNR value) of 29 dB. High frequency: 32 dB Medium frequency: 26 dB Low frequency: 19 dB. Note: See the guide to choosing hearing protection with the right attenuation value.

Sizes:

| STR. | ART. NO. | EAN |
|----------|----------|---------------|
| One size | 91365 | 5701952913657 |

Minimum sales and packaging:

| MINIMUM ORDER | PK. | KLL. |
|---------------|-----|--------|
| 1 stk | N/A | 20 stk |

| EN standards | EN 352-1 EN 352-6 EN 352-8 |
|--------------|---|
| Certificates | C CAT. III REACH |
| Features | BLUETOOTH® AUX BUILT-IN CONNECTION MICROPHONE CONTROL SNR VALUE |