Art. no.: 92891



# **OX-ON Fall Protection Kit Supreme V33 L/XL**



#### Features:

- Complete set
- Padding on the shoulders and thighs
- Edge-tested work line
- User-friendly click buckles
- · Stainless steel zipper

## **Colours:**

black, orange

#### **Product Description:**

OX-ON Fall Protection Kit Supreme is an exclusive and extremely user-friendly fall protection kit that is suitable for those who have demanding work tasks, e.g. during scaffolding/roofing work. In the bag you will find the OX-ON V33 Adventure Power Harness Supreme: A top-class 2-point harness with click buckles and padding on the shoulders and thighs. OX-ON Fall Arrester Supreme: An effective fall arrester with 10 meters of abrasion-resistant edge-tested work line and stainless steel slide lock. OX-ON Webbing Sling Comfort 1.2 m: An anchoring strap for the fall protection. The OX-ON V33 Body Harness adjusts quickly and perfectly to the body with a number of adjustment points, so you are guaranteed maximum comfort and freedom of movement in your work. The effective click buckles make it easy for you to put/take the harness on and off, and a strong D ring on the back and near the chest ensures good and solid anchoring - as well as easy connection. The OX-ON V33 body harness is also equipped with comfortable padding at the shoulders and thighs, which gives you optimal support and comfort in connection with your work. The harness is made of a robust reflective 2-color webbing tape which is surface-treated to protect against oil and dirt, which makes the harness particularly dirt-repellent and easy to clean and maintain. The body harness is tested for 150 kg. With the OX-ON Fall Arrester Supreme, you get an effective fall arrester package and a robust rope zipper in stainless steel with an autolock carabiner mounted on 10 meters of edge-tested core

## Sizes:

STR.	ART. NO.	EAN	
L/XL	92891	6425670037424	

# Minimum sales and packaging:

MINIMUM ORDER	PK.	KLL.
1 stk	N/A	6 stk

EN standards	EN 353-2 EN 354 EN 358 EN 361 EN 362 EN 795 EN 566 EN 353-2 S
Certificates	C CAT. III REACH
Features	EDGE TESTED (7 2 3.5mm)  EDGE TESTED



#### **Product Description:**

sheath rope (12mm) with high wear resistance, and with properties that prevent the rope from twisting. The rope and the zipper give you freedom of movement and safety at the same time, as the rope slide stops you immediately in the event of a fall. The rope is for vertical use, and the fall arrester package releases a maximum energy absorber of 1 meter. The lower part of the rope should be attached or equipped with a counterweight. OX-ON Webbing Sling Comfort 1.2 meters gives you a compact and fast solution when you need to anchor your fall protection. The polyester strap is 26 mm wide, it takes up minimal space and it is extremely easy to use. The webbing tape has a breaking strength of >30kN. You get the whole set in the practical OX-ON Backpack sized M. Ø 25x42 cm. The anchorage point should, if possible, be above head height to reduce the ground clearance. Note that the ground clearance must be calculated at all times before starting work with fall protection. For further information on the required ground clearance, refer to the enclosed user manual or contact OX-ON.